



PACKAGING REELS

7" LOKREEL® Mini RJ Component Packaging Reels



Advantek 7" Mini RJ component packaging reels provide excellent protection when shipping small components packaged in carrier tape, such as bare die and small integrated circuit packages. Made from general-purpose and high-impact polystyrene for added strength and durability, our 7" reels are available in a variety of widths, with anti-static coatings.

- Available in 8, 12, 16, 24 and 32 mm widths
- Reel flange accommodates labels up to 2" x 4"
- Available with Anti-static coated (WT/BL/BK) or with carbon additive(DBK)
- Reels may be ordered in white, blue or black

Configuration

Advantek LOKREEL® Mini RJ7xx reels have an outside diameter of 7" (180mm) and a 1/2" (13mm) diameter arbor hole. Reel hubs measure 2.36" (60mm) in diameter.

The 7" Mini RJ7xxDBK is compliant with EIAJ standard in terms of dimension and surface resistivity.

Shelf Life and Storage

We recommend that Advantek LOKREEL® Mini reels be used within two years from the date of manufacture. Store this product in its original packaging in a climate-controlled environment where temperature ranges from 21° C +/- 17°C (70°F +/- 30°F). Allow the product to stabilize at room temperature prior to use. The mechanical integrity of the product is not affected by humidity.

RJ7xx Part Numbers

	White	Blue	Black	Black with SR _{≤10} ⁹
8mm	RJ708WT	RJ708BL	RJ708BK	RJ708DBK
12mm	RJ712WT	RJ712BL	RJ712BK	RJ712DBK
16mm	RJ716WT	RJ716BL	RJ716BK	RJ716DBK
24mm	RJ724WT	RJ724BL	RJ724BK	RJ724DBK
32mm	RJ732WT	RJ732BL	RJ732BK	RJ732DBK

Note: Please contact with Advantek sales for availability.

Material Properties of 7" LOKREEL® Mini RJ Reels

Property	Typical Value	Test Method/Standard
Tensile Strength	20 Mpa	ISO 572
Elongation	40%	ISO 572
Flexural Modulus	1360 Mpa	ISO 178
Vicat Softening	82°C	ISO 306
Specific Gravity	1.03 g/cc	ISO 1183
Surface Resistivity	DBK: $\leq 10^9$ ohms/sq. WT/BL/BK: $< 10^{12}$ ohms/sq.	ASTM D 257 EIA 541

Note: The values presented for this product are typical laboratory data and may be changed without notice.



Our wide line of component packaging products offers the flexibility you need to balance price and performance.



ADVANTEK
engineered confidence™

Embossed Carrier Tapes	SFT®	Complex Designs	Basic Designs	Interleaf Tapes			
Cover Tapes	Heat Activated	Pressure Sensitive					
Packaging Reels	Jumbo	Ultra	Pro	Lite	Trimline	Mini	
Barrier Bags	DRYLOK®	STATLOK®					
Bands	PROBAND®	LOKBAND®					
Humidity Indicator Cards	1 Spot	3 Spot	4 Spot	6 Spot			
Desiccant	1/6 Unit	1/3 Unit	1/2 Unit	1 Unit	2 Unit	4 Unit	8 Unit

Germany: +49-761-45546-0
 North America: +1-510-623-1877
 Philippines: +63-49-545-6350
 Singapore: +65-6759-6800
 China: +86-21-5048-4588
 Taiwan: +886-2-2290-1789
 Japan: +81-49-229-5100

advantek.com