



EMBOSSED CARRIER TAPES

# Homogenous PS+C Type P Carrier Tape



Advantek's PS+C (polystyrene plus carbon) carrier tape is a specially modified static dissipative polystyrene offering good strength and stability over time and temperature variations for a limited range of tape designs. This material is suitable for high volume (>1Million meters per year) carrier tapes at pre-determined standard reel lengths. The P material offers exceptional protection at a lower cost than our standard C material. It is currently available in 0.30mm thickness.

### Shelf Life and Storage

We recommend that Advantek PS+C carrier tapes be used within 5 years from the date of manufacture. Store this product in its original packaging in a climate-controlled environment where temperature ranges from 21°C +/- 17°C (70°F +/- 30°F). This product is not affected by humidity. Allow the product to stabilize at room temperature prior to use.

### Camber

The Advantek Homogeneous PS+C series meets the EIA-481-D standard for camber that is not greater than 1mm in 250 linear millimeters. For 8mm to 24mm carrier tape in the level wind format, the camber will not be greater than 2mm in 250 linear millimeters.

Homogenous PS+C Carrier Tape Material Properties

	Type P	Test Method
Standard Thickness	0.30mm	
Specific Gravity	1.06 g/cc	ASTM D-792
Elongation	LD 90%	ASTM D-882 [5]
Tensile Strength	LD 3840 psi	ASTM D-882 [5]
Vicat Softening	>95°C (203°F)	ASTM D-1525
Surface Resistivity	<10 <sup>12</sup> ≥ 10 <sup>5</sup> ohms/square	ASTM D-257 Static Dissipative per EIA 541

Note: The values presented for this product are typical laboratory data and may be changed without notice.

Material Ionics Data (ppm)

Halogen-Fluorine (F)	ND
Halogen-Chlorine (Cl)	ND
Halogen-Bromine (Br)	ND
Phosphorus (P)	158
Sulfur (S)	ND
Lithium (Li)	ND
Sodium (Na)	ND
Potassium (K)	ND
Magnesium (Mg)	ND
Calcium (Ca)	28

Note: The above ionics data was measured by an independent laboratory.

COVER TAPE COMPATIBILITY

MATERIAL	AA	AHP	ABX	AD0	PS3	APC	AHPC
P Type Homogenous (Polystyrene + Carbon)	X	X	X	X	X		



Our wide line of component packaging products offers the flexibility you need to balance price and performance.



**ADVANTEK**  
engineered confidence™

Embossed Carrier Tapes	SFT®	Complex Designs	Basic Designs	Interleaf Tapes		
Cover Tapes	Heat Activated		Pressure Sensitive			
Packaging Reels	Pro	Ultra	Lite	Trimline		
Barrier Bags	DRYLOK®		STATLOK®			
Bands	PROBAND®		LOKBAND®			
Humidity Indicator Cards	1 Spot	3 Spot	4 Spot	6 Spot		
Desiccant	1/3 Unit	1/2 Unit	1 Unit	2 Unit	4 Unit	8 Unit
Dicing Tapes	UV Cured		Non UV Cured			

Germany: +49-761-45546-0  
 North America: +1-510-623-1877  
 Philippines: +63-49-545-6350  
 Singapore: +65-6759-6800  
 China: +86-21-5048-4588  
 Taiwan: +886-2-2290-1789  
 Japan: +81-49-229-5100

advantek.com