



BANDS
PROBAND™



Advantek PROBAND™ is a protective band made of carbon-loaded polystyrene designed to be wound around the diameter of standard size shipping reels of loaded carrier tape. The band covers the outermost wrap of carrier tape to provide added protection for packaged components. The bands are slightly wider than the carrier tape, preventing the flanges from crushing together during dry-pack or handling to protect packaged components from impact damages.

- Available in EIA standard carrier tape width from 8mm to 88mm
- Complete protection for devices when used with the Advantek LOKREEL® and LOKBAND®.
- Tighter-controlled SR version is available
- Available in lengths to fit standard size shipping reels

Shelf Life and Storage

We recommend that Advantek PROBAND™ be used within 5 years from the date of manufacture. Store this product in its original packaging in a climate-controlled environment where temperature ranges from 21°C +/- 17°C (70°F +/- 30°F). Allow the product to stabilize at room temperature prior to use. The mechanical integrity of the product is not affected by humidity.

Configurations

Advantek PROBAND™ is available in various lengths to navigate the circumference of standard diameter reels. The width of the PROBAND™ depends upon the width of the carrier tape used. The following table shows PROBAND™ part numbers with width and thickness for standard carrier width of between 8mm to 88mm. Custom width and thickness is available upon request.

PROBAND™ Part Numbers				
Part Number	Length(+/-0.03m) XXX:	Width(+0.7/-0.0mm) YY:	Thickness (+/-0.1mm)	
PBXXYYUC	057=0.57m; 060=0.6m; 063=0.63m; 109=1.09m; 117=1.17m; 120=1.2m; 140=1.4m; 143=1.43m; 218=2.18m.	08=8.3; 12=12.3; 16=16.3; 24=24.3; 32=32.3; 44=44.3; 56=56.3	1.0	
PBXXYYST			1.0	
PB050XXYY			0.5	
PBXXYYUCDBK			1.0	
PBXXYYSTDBK			1.0	
PB050XXYYDBK			0.5	
PBXXYYUC			72=72.3 88=88.3	1.0
PBXXYYUCDBK			1.0	

Note:
1. P/Ns with the suffix of 'ST' are only for Taiwan market.

PROBAND™ Material Properties		
Property	Typical Value	Test Method/Standard
Surface Resistivity Surface Resistance	<10 ¹² ≥10 ⁵ ohms/square DBK suffix: <10 ⁹ ≥10 ⁰ Ohms.	ASTM D-257 ANSI/ESD STM11.13
Tensile Strength	3700 PSI	ASTM D-882
Elongation	40%	ASTM D-882
Specific Gravity	1.06 g/cc	ASTM D-792
Shelf Life	5 years	N/A
Color	Black	N/A

Note: The values presented for this product are typical laboratory data and may be changed without notice.



Our wide line of component packaging products offers the flexibility you need to balance price and performance.



ADVANTEK®
engineered confidence™

Embossed Carrier Tapes	SFT®	Complex Designs	Basic Designs	Interleaf Tapes			
Surftape®	Bare Die	Micro Thin					
Cover Tapes	Heat Activated	Pressure Sensitive					
Packaging Reels	Jumbo™	Ultra™	Pro™	Lite™	Trimline™	Mini	
Barrier Bags	DRYLOK®	STATLOK®					
Bands	PROBAND®	LOKBAND®					
Humidity Indicator Cards	1 Spot	3 Spot	4 Spot	6 Spot			
Desiccant	1/6 Unit	1/3 Unit	1/2 Unit	1 Unit	2 Unit	4 Unit	8 Unit

- Germany: +49-761-45546-0
- North America: +1-510-623-1877
- Philippines: +63-49-545-6350
- Singapore: +65-6759-6800
- China: +86-21-5048-4588
- Taiwan: +886-2-2290-1789
- Japan: +81-49-229-5100

advantek.com