



VAPLOK™ Desiccants



Advantek VAPLOK™ Desiccants protect moisture-sensitive devices by absorbing airborne moisture particles which may be present inside a moisture barrier bag after vacuum packaging.

- Meets EIA Std. 583 and MIL-D-3464, Type I and II.
- Use with Advantek Humidity Indicator cards and DRYLOK® Moisture Barrier Bags for superior protection
- Desiccant material can be either Clay or Silica Gel

Construction

VAPLOK™ Desiccants are made of Montmorillonite (bentonite) Clay or Silica Gel desiccant material packaged in printed, non-dusting, sulphur-free Tyvek® substrates.

Configurations

Advantek VAPLOK™ Desiccants are available in several formats designed for small and large applications. Bag sizes vary from 1/3 unit packs to 8 unit packs. A unit of desiccant (33 grams) refers to its drying capacity, not its volume, and is the amount of desiccant which will absorb at least 3 grams of water vapor at 20% relative humidity and at least 6 grams of water vapor at 40% RH at 77F (25C). The product is shipped in airtight packaging to prevent exposure to moisture.

Absorption rate at 10% RH, 77°F (25°C)

Clay = 2.8g
Silica Gel = 1.99g

Shelf Life and Storage

We recommend that VAPLOK™ desiccant products be used within 12 months of manufacture. Store this product in its original packaging in a climate-controlled environment where temperature ranges from 20°C +/- 16°C (68°F +/- 61°F) and relative humidity is 50% +/- 30%. Exceeding these recommended storage conditions could result in inconsistent product performance.

Clay/Tyvek®

Bag Size	Bags Per Container	Part Number
1/3 Unit	700	DES1/3P
1/2 Unit	550	DES1/2P
1 Unit	300	DES1P
1 Unit	1300	DES1D
2 Unit	150	DES2P
2 Unit	800	DES2D
4 Unit	500	DES4D
8 Unit	300	DES8D

Silica Gel/Tyvek®

Bag Size	Bags Per Container	Part Number
1/2 Unit	550	SIG1/2P
1 Unit	1800	SIG1D
1 Unit	300	SIG1P
2 Unit	800	SIG2D
2 Unit	150	SIG2P

Note:
P = Pail
D = Drum



Our wide line of component packaging products offers the flexibility you need to balance price and performance.



ADVANTEK®
engineered confidence™

Embossed Carrier Tapes	SFT™	Complex Designs	Basic Designs	Interleaf Tapes		
Cover Tapes	Heat Activated	Pressure Sensitive				
Packaging Reels	Pro	Ultra	Lite	Trimline		
Barrier Bags	DRYLOK®	STATLOK®				
Bands	PROBAND™	LOKBAND™				
Humidity Indicator Cards	1 Spot	3 Spot	4 Spot	6 Spot		
Desiccant	1/3 Unit	1/2 Unit	1 Unit	2 Unit	4 Unit	8 Unit
Dicing Tapes	UV Cured	Non UV Cured				

Germany: +49-761-45546-0
North America: +1-510-623-1877
Philippines: +63-49-545-6350
Singapore: +65-6759-6800
China: +86-21-5048-4588
Taiwan: +886-2-2290-1789
Japan: +81-49-229-5100

advantek.com