



## BARRIER BAGS

# DRYLOK® 4400 Static Shielding/ Moisture Barrier Bag




The DRYLOK® 4400 from Advantek® is a transparent polyester ESD static shielding/moisture barrier bag. This distinctive transparent bag uses a unique aluminum vapor coating layer, providing protection to bag contents from both electro-static shock and moisture.

DRYLOK® 4400 bags are available in several standard sizes designed to contain matrix trays, tubes and 13" shipping reels and custom sizes can be made to fit the needs of nearly any project. When used with the Advantek® Desiccant and Humidity Indicator Cards, The DRYLOK® 4400 bags provide superior protection for Static- and moisture-sensitive devices.

- 3.3 mil thick transparent polyester construction to provide inspection capability with good puncture protection
- Meets requirements of EIA 541 & EIA 583
- Strong puncture resistance ensures vacuum seal integrity and protects contents of bag for up to 2 years

### Construction


DRYLOK® 4400 Static Shielding / Moisture Barrier Bags are constructed in seven layers. These consist of a static dissipative outer layer followed by a polyester film layer and a proprietary aluminum vapor coat. In the middle is a second polyester layer followed by an adhesive layer. Rounding out the DRYLOK® 4400 is a polyethylene layer and a final static dissipative coating.



### Configurations

DRYLOK® 4400 Static Shielding/Moisture Bags are available in custom sizes or in several industry standard sizes designed for 13" reels, matrix trays and tubes. Bags have a 2-seal configuration with a bottom fold or a 3-seal configuration, each with our standard Advantek® hot-stamp or your company's hot-stamped or flexographically printed logo.

### Typical Bag Configuration



### Shelf Life and Storage

We recommend that DRYLOK® 4400 bags be used within 2 years from the date of manufacture. Store this product in its original packaging in a climate-controlled environment where temperature ranges from 20°C +/- 16°C (68°F +/- 61°F) and relative humidity is 50% +/- 30%. Exceeding these recommended storage conditions could result in inconsistent product performance.

### DRYLOK® 4400 Physical Properties

Property	Typical Value	Test Method/Standard
Thickness	3.3 mils ± 10%	N/A
Puncture Resistance	> 20 lbs	FTMS 101C MTH 2065
Seam Strength	Pass	MIL-PRF-81705D
Light Transmission	>40%	ASTM D 1003
MVTR	<0.05 grams	ASTM F 1249

### DRYLOK® 4400 Electrical Properties

Surface Resistivity Interior Exterior	<10 <sup>12</sup> ohms/square <10 <sup>12</sup> ohms/square	ASTM D 257 ASTM D 257
Static Decay	< 2 second	EIA 541
Static Shielding	<20 volts	EIA 541

Note: These values were developed from random samples taken from production material, and may be changed without notice. We believe them to be typical for the product. However, actual values may vary somewhat from those depicted above. You should determine product suitability based upon your own internal criteria.



Our wide line of component packaging products offers the flexibility you need to balance price and performance.



**ADVANTEK®**  
engineered confidence™

Embossed Carrier Tapes	SFT®	Complex Designs	Basic Designs	Interleaf Tapes			
Cover Tapes	Heat Activated		Pressure Sensitive				
Packaging Reels	Jumbo	Ultra	Pro	Lite	Trimline	Mini	
Barrier Bags	DRYLOK®		STATLOK®				
Bands	PROBAND®		LOKBAND®				
Humidity Indicator Cards	1 Spot	3 Spot	4 Spot	6 Spot			
Desiccant	1/6 Unit	1/3 Unit	1/2 Unit	1 Unit	2 Unit	4 Unit	8 Unit

Germany: +49-761-45546-0  
 North America: +1-510-623-1877  
 Philippines: +63-49-545-6350  
 Singapore: +65-6759-6800  
 China: +86-21-5048-4588  
 Taiwan: +886-2-2290-1789  
 Japan: +81-49-229-5100

advantek.com