




## COVER TAPES

# Type HUC Heat Activated Antistatic Cover Tape



Advantek's Type HUC Cover Tape is an antistatic, transparent, heat sealable cover film. It is engineered to protect and contain surface mount components in embossed polystyrene and polycarbonate carrier tapes.

- Transparent to allow post-taping inspection of components while in the pocket
- Formulated to prevent wetting
- Suitable for any heat sealing taping application
- Consistent adhesion
- Complies with EIA-481 standards
- Proven to perform with these Advantek Carrier Tape materials:
  - Polystyrene, Homogenous Polystyrene
  - Polycarbonate
- Available in level winding

### Construction

Type HUC Cover Tape contains a top layer of antistatic PET base film, and a bottom layer of heat activated adhesive coating layer. Both sides are antistatic to ensure the protection of static sensitive devices.

### Configurations

Type HUC Heat Activated Cover Tape is provided standard with 300, 500 and 1000 splice-free meters. longer meter length in level winding is available: 5.\*mm in 3000 meters, 9.\*mm in 1500 or 3000 meters. Widths available include all EIA standard widths for carrier tapes between 8mm and 56mm, plus custom widths by special request.

Part Number	Width
HUC0054-300	5.4mm +/- 0.1
HUC0054-3000	5.5mm +/- 0.1
HUC0092-300	9.2mm +/- 0.1
HUC0092-1500	9.2mm +/- 0.1
HUC0092-3000	9.2mm +/- 0.1
HUC0133-300	13.3mm +/- 0.1
HUC0135-300	13.5mm +/- 0.1
HUC0213-300	21.3mm +/- 0.1
HUC0255-300	25.5mm +/- 0.1
HUC0375-300	37.5mm +/- 0.1
HUC0495-300	49.5mm +/- 0.1

Note: The part numbers listed here are just examples, you may check Advantek sales for the availability of other width and length.

### Recommended Sealing Conditions (Single-Strike Seal Mode)

Temperature	150° - 200°C
Dwell Time	0.02 - 0.40 sec.
Pressure	30 - 70 PSI
Seal Rail Width	0.015 - 0.020" (0.38 - 0.51mm)

### Material Properties

Property	Typical Value	Test Method/Standard
Thickness	0.050 mm	N/A
Adhesion to Carrier	45+/-15'	EIA-481
Surface Resistivity ( 23±2C; 50±5%RH)	Adhesive: ≤10 <sup>10</sup> Ohms/sq. back side: ≤10 <sup>11</sup> Ohms/sq.	ASTM D-257
Tensile Strength	11000 PSI	ASTM D-882
Elongation	95%	ASTM D-882
Transparency	90% Transmittance 89% Clarity 22% Haze	ASTM D-1003
Color	Transparent	

Note: The values presented for this product are typical laboratory data and may be changed without notice. \*Tests performed under specific sealing conditions.

### Shelf Life and Storage

We recommend that the Advantek HUC Cover Tape be used within 24 months from the date of manufacture. Store this product in its original packaging in a climate-controlled environment with temperatures under 30°C and relative humidity below 65%. Do not store in direct sunlight or excess temperature/humidity for prolonged periods of time. Allow the product to stabilize at room temperature prior to use.



Our wide line of component packaging products offers the flexibility you need to balance price and performance.



**ADVANTEK**  
engineered confidence™

Embossed Carrier Tapes	SFT®	Complex Designs	Basic Designs	Interleaf Tapes			
Surftape®	Bare Die	Micro Thin					
Cover Tapes	Heat Activated	Pressure Sensitive					
Packaging Reels	Jumbo™	Ultra™	Pro™	Lite™	Trimline™	Mini	
Barrier Bags	DRYLOK®	STATLOK®					
Bands	PROBAND®	LOKBAND®					
Humidity Indicator Cards	1 Spot	3 Spot	4 Spot	6 Spot			
Desiccant	1/6 Unit	1/3 Unit	1/2 Unit	1 Unit	2 Unit	4 Unit	8 Unit

Germany: +49-761-45546-0  
 North America: +1-510-623-1877  
 Philippines: +63-49-545-6350  
 Singapore: +65-6759-6800  
 China: +86-21-5048-4588  
 Taiwan: +886-2-2290-1789  
 Japan: +81-49-229-5100

advantek.com